



# TECHNICAL SPECIFICATIONS

## Top Down

P E T O D O R R E M O V E R

Top Down is a cutting edge highly concentrated odor remover. It can safely remove pet odors from all types of existing flooring. Specially designed to penetrate seams, grout lines and edge joints in all types of hard surface flooring. Top Down is a live enzyme product that will consume all pet odors at the source and leave the flooring clean and streak-free.

### SAFE TO USE ON:

- Vinyl plank
- Vinyl tile
- Ceramic floors
- Grout lines
- Sheet vinyl
- Laminate floors
- Prefinished hardwoods
- Cork floors
- Concrete floors

### PRODUCT SPECIFICATIONS:

- 100% Biodegradable
- Safe to use around pets
- 100% non-hazardous
- Flammability: None
- One-year shelf life

### PACKAGING SPECIFICATIONS:


- 35 lbs. per case
- 4 gallons per case
- 36 cases per pallet (144 gallons)

### APPLICATION INSTRUCTIONS:

Using a pump-up sprayer, generously spray affected area. Using a sponge mop, immediately mop the entire area, going across (in the opposite direction of all seams or grout joints). After working Top Down into all seams, dry mop the area to remove all remaining product on surface. Repeat this process until odor is removed completely.



### NFPA CODES





# TECHNICAL SPECIFICATIONS

## Top Down

P E T O D O R R E M O V E R

Top Down is a cutting edge highly concentrated odor remover. It can safely remove pet odors from all types of existing flooring. Specially designed to penetrate seams, grout lines and edge joints in all types of hard surface flooring. Top Down is a live enzyme product that will consume all pet odors at the source and leave the flooring clean and streak-free.

### SAFE TO USE ON:

- Vinyl plank
- Vinyl tile
- Ceramic floors
- Grout lines
- Sheet vinyl
- Laminate floors
- Prefinished hardwoods
- Cork floors
- Concrete floors

### PRODUCT SPECIFICATIONS:

- 100% Biodegradable
- Safe to use around pets
- 100% non-hazardous
- Flammability: None
- One-year shelf life

### PACKAGING SPECIFICATIONS:

- 35 lbs. per case
- 4 gallons per case
- 36 cases per pallet (144 gallons)

### APPLICATION INSTRUCTIONS:

Using a pump-up sprayer, generously spray affected area. Using a sponge mop, immediately mop the entire area, going across (in the opposite direction of all seams or grout joints). After working Top Down into all seams, dry mop the area to remove all remaining product on surface. Repeat this process until odor is removed completely.



### NFPA CODES

